

BUNDED OIL TANKS Secure Storage

Harlequin®
StorageTanks®

RELIABLE CONTAINERS

Harlequin Bunded Oil Tanks

The Harlequin range of Bunded Oil Tanks are available from 650 litres, up to 9,250 litre models. Each tank has been designed and manufactured to exceed the most technical, environmental and regulatory requirements. Available as a tank only HQI model, tank and tankpack ITE model, or top outlet ITT model.

What is a Bunded Oil Tank?

A 'Bunded' oil tank simply consists of a tank within a tank. Oil is stored in the inner tank and the outer tank acts as a failsafe so that in the event of a spillage, excess oil will collect in the outer tank - thus averting a pollution incident and costly environmental clean-up operation.

Bunded oil tanks have been proven to significantly reduce the risk of pollution at oil storage installations. They are a requirement at most commercial, industrial and institutional premises; all installations in the Channel Islands; and, at many domestic installations in the United Kingdom and Republic of Ireland.

Benefits of a Harlequin Bunded Oil Tank:

- **More Options** - the full range has 15 options of tank size, a tank to suit every installation requirement.
- **Integrally Bunded** - designed to protect the surrounding environment, all tanks are bunded preventing pollution if the internal tank was ever to leak.
- **Non Corrosive** - manufactured from Medium Density Polyethylene (MDPE) your Harlequin tank will not corrode.
- **10 Year Guarantee** - peace of mind that should an issue arise with your tank, Harlequin will be there to help. *10 year guarantee upon registration with Harlequin.
- **Meets Regulations** - as well as being fully bunded, each tank meets all relevant regulatory requirements.
- **Contents Monitoring** - each model has a 32mm hole suitable for fitting an electronic gauge. Gauge is standard with ITE and ITT models



All tanks are fully bunded and meet all regulatory requirements.

ABOUT HARLEQUIN MFG

Being one of Europe's largest manufacturers of rotationally moulded plastic tanks, we've been at the forefront of product developments for over 35 years. From our base in Northern Ireland we design, manufacture and deliver our tanks all over the world.

With your Harlequin tank you can be assured you have the best solution for your needs. Our unrivalled reputation for quality is backed up by our 9001, 14001 and 18001 Management System Certifications.

Visit our website to find out about our full range of products:

Fuel/Diesel Tanks | Hot Water Storage | AdBlue Tanks | Water Tanks | Rainwater Harvesting | Sewage Treatment | Bunkers



Follow Us:
@HarlequinMFG



For the latest product information, give us a call or visit our website:

T 028 9261 1077 E Info@harlequin-mfg.com
www.harlequinplastics.co.uk

Harlequin®
MANUFACTURING FOR TOMORROW

Bunded Oil Tanks

The Harlequin range of Bunded Oil Tanks are manufactured to exceed the most demanding technical, environmental and regulatory requirements. Available from 650 litres right up to 9,250 litre models, each tank is CE marked where appropriate with Declarations of Performance available on request.



650 HQi / ITE / ITT
SLIMLINE
Length 1,715mm
Width 670mm
Height 1,330mm
Capacity 673 litres
Weight 116kg

OFCERT License no: 0644051004R



1000 HQi / ITE / ITT
SLIMLINE
Length 2,150mm
Width 690mm
Height 1,420mm
Capacity 1,055 litres
Weight 132kg

OFCERT License no: 0644051005R



1100 HQi / ITE / ITT
SLIMLINE
Length 1,880mm
Width 890mm
Height 1,595mm
Capacity 1,097 litres
Weight 135kg

OFCERT License no: 0644010901R



1200 HQi / ITE / ITT
LOW PROFILE
Length 1,900mm
Width 1,600mm
Height 960mm
Capacity 1,317 litres
Weight 130kg

OFCERT License no: 0644031201



1225 HQi / ITE / ITT
SLIMLINE
Length 2,110mm
Width 840mm
Height 1,525mm
Capacity 1,248 litres
Weight 150kg

OFCERT License no: 0644081802



1300 HQi / ITE / ITT
SLIMLINE
Length 2,100mm
Width 950mm
Height 1,540mm
Capacity 1,344 litres
Weight 170kg

OFCERT License no: 0644051006R



1400 HQi / ITE / ITT
HORIZONTAL
Length 1,900mm
Width 1,250mm
Height 1,420mm
Capacity 1,452 litres
Weight 135kg

OFCERT License no: 0644010902R



1450 HQi / ITE / ITT
VERTICAL
Diameter 1,560mm
Height 1,590mm
Capacity 1,498 litres
Weight 112kg

OFCERT License no: 0644010903R



2000 HQi / ITE / ITT
HORIZONTAL
Length 2,360mm
Width 1,315mm
Height 1,415mm
Capacity 2,092 litres
Weight 180kg

OFCERT License no: 0644010904R

NEW



2500 HQi / ITE / ITT
HORIZONTAL
Length 2,460mm
Width 1,435mm
Height 1,470mm
Capacity 2,571 litres
Weight 215kg

OFCERT License no: 0644051003R



2525 HQi / ITE / ITT
SLIMLINE
Length 2,450mm
Width 1,200mm
Height 1,685mm
Capacity 2,550 litres
Weight 235kg

OFCERT License: Pending



3500 ITE / ITT
HORIZONTAL
Length 2,450mm
Width 1,770mm
Height 1,890mm
Capacity 3,471 litres
Weight 275kg

OFCERT License no: 0644031202



5400 ITE / ITT
VERTICAL
Diameter 2,575mm
Height 2,100mm
Capacity 5,307 litres
Weight 325kg

OFCERT License no: 0644010318R



7500 ITE / ITT
VERTICAL
Length 2,940mm
Width 2,305mm
Height 2,820mm
Capacity 8,088 litres
Weight 505kg

OFCERT License no: 0644121703



9,250 ITE / ITT
VERTICAL
Length 3,140mm
Width 2,510mm
Height 2,820mm
Capacity 9,382 litres
Weight 600kg

OPTION 1: HQi
Bunded Oil Tank only.

Specification:

- Integrally bunded
- Bottom outlet with 1" BSP(F) thread
- 16" lockable access lid
- 4" lockable inspection cap (fill point for 350 model)
- 2" BSP(M) fill point (excludes 350 model)
- 32mm hole with cover for electronic gauge
- Inner tank vent (excludes 350 model)

Additional to specific models:

- Mechanical overfill prevention valve (3500, 5400, 7500 models)

OPTION 2: ITE
Bunded Oil Tank with gauge and bottom outlet kit.

Specification:

- Integrally bunded
- Bottom outlet with 1" BSP(F) thread
- 16" lockable access lid
- 4" lockable inspection cap
- 2" BSP(M) fill point
- 32mm hole with cover for electronic gauge
- Inner tank vent
- Ultrasonic contents gauge with remote display
- Bottom outlet fitting kit
- LRC overfill prevention probe

Additional to 3500, 5400, 7500, 9250 models:

- Mechanical overfill prevention valve
- Bund Monitor

OPTION 3: ITT
Bunded Oil Tank with top outlet & gauge.


Specification:

- Integrally bunded
- Tanktop top offtake fitting*
- 16" lockable access lid
- 4" lockable inspection cap
- 2" BSP(M) fill point
- 32mm hole with cover for electronic gauge
- Inner tank vent
- Ultrasonic contents gauge with remote display
- LRC overfill prevention probe

Additional to 3500, 5400, 7500, 9250 models:

- Mechanical overfill prevention valve
- Bund Monitor

* 5400, 7500, 9250 models fitted with Ecoflex top offtake fitting



Top Outlet

Please Note: All tank capacities are brimful. All OFCERT license numbers are for ITE models, ITT OFCERT license numbers are available on the OFTEC website. All information contained herein is understood to be correct at time of publication. Harlequin reserve the right to amend product specification without notice.

For the latest product information, give us a call or visit our website:

T 028 9261 1077 E Info@harlequin-mfg.com
www.harlequinplastics.co.uk

Your accredited Harlequin Reseller:



or contact us to find your nearest reseller: 028 9261 1077